



TITAN 2200

CHARACTERISTICS

Description	Size / Thickness
Plank Size 7" Wide x 48" Long (Registered & Embossed)	6.5mm Total Thickness
Plank Size 8.86" Wide x 48" Long (Registered & Embossed)	5.0mm Core + 1.5mm IXPE + 0.5mm Wearlayer
Plank Size 9.0" x 60" Long (Registered & Embossed)	
Heat Resistance & Color Stability	ASTM F1514 - After 7 days of accelerated heat in the chamber, No Change occurred.
Color Change - Light Stability	ASTM F1515 - 150 Hours Direct accelerated light - Resulting in nearly No Change
Impact Resistance	ASTM F1914 - 0.002" after 60min recovery time - Surface Integrity - No puncture through wear layer
Static Load Limit	ASTM F1914 - Results 0.002" - Exceeding Classification (34) requirements
Castor Chair Resistance	ISO4918 - Classification (34) No visible damage effects from furniture leg testing.
Approximate IIC Rating on 6" Thick Concrete Slab Floor (150 lbs/cu ft)	IIC: 62 with drop ceiling
Resistance to Chemical	ASTM F925 - No change occurred to product after exposure
Fire Rating	ASTM E648 - Results "Exceeds Class 1 rating as specified in NFPA Life Safety Code 101"
Peel Strength ISO 24345:2006	Mean Value: MD 110 N/50mm; AMD 105 N/50mm
Fungi Resistance ASTM G21-15	Unlike Cork, this product shows zero "None" results for observed growth.
FloorScore	SCS-FS-04026

INSTALLATION

Click System - Floating

PACKAGING

Content of Box	Content of Pallet
(7" x 48" - 18.91 Sq.Ft. / Box)	7" Profile: 55 cartons - 2,151.60 lbs
(8.86" x 48" - 17.73 Sq.Ft. / Box)	8.86" Profile: 56 cartons - 2,053.52 lbs
(9" x 60" - 14.76 Sq.Ft. / Box)	9" Profile: 96 cartons - 3,307.20 lbs

Warranty

- Lifetime Residential Wear Warranty
- Lifetime Structural Warranty
- Lifetime Waterproof Warranty
- 10 Year Limited Light Commercial Warranty

Specifications subject to change. Contact Peoples Floors for current details.